

#### Notified Body No. 1019 VVUÚ, a.s., Pikartská 1337/7, 716 07 Ostrava – Radvanice, Czech Republic www.vvuu.cz; e-mail: cov@vvuu.cz

## **EU type-examination certificate**

according to Article 19 (c) of Regulation (EU) 2016/425 of the European Parliament and of the Council

No.: 1019-156/Q/2021

| Manufacturer:                                     | Nal Hon Industrial Co., Ltd., No. 418, Hsi-Hu Road, Ta-Li<br>District, 41263 Taichung City, Taiwan   |  |
|---|--|--|
| Product:  | Aluminum Scaffold Hook, type YAH005  |  |
| PPE category:                                     | III.   |  |
| Applied standards and/or technical specification: | ČSN EN 362:2005 (identical to EN 362:2004)<br>ČSN EN 365:2005 (identical to EN 365:2004)   |  |
| Base for issue of certificate:                    | Evaluation report No. 1019-020279/2021 (integral part of this certificate)   |  |
| Conditions of validity:                           | Certificate shall only be used in conjunction with one of the conformity assessment procedures referred to Article 19 (c) point i) or ii) of Regulation (EU) 2016/425 of the European Parliament and of the Council. |  |
| Validity of certificate till:                     | 2026-05-17   |  |

VVUÚ, a.s. hereby certifies that the sample of the product mentioned above meets all the relevant essential health and safety requirements of Annex II of the Regulation (EU) 2016/425 of the European Parliament and of the Council.



2021-05-18 Date of issue Ing. Tomáš Dorazil Deputy Director NB 1019

Duplication of only parts of this document is subject to the approval of VVUÚ, a.s., NB 1019, Ostrava - Radvanice, Czech Republic.



# Notified Body No. 1019 VVUÚ, a.s., Pikartská 1337/7, 716 07 Ostrava – Radvanice, Czech Republic www.vvuu.cz; e-mail: cov@vvuu.cz

### **Description of product**

| Material:                 | Aluminum Alloy 6066 |
|---------------------------|---------------------|
| Gate Closing:             | Self-closing        |
| Gate Locking:             | Self-locking        |
| Min. Gate Opening:        | 58 mm               |
| Min. Static Strength (↔): | 35 kN               |
| Class (acc. to EN 362):   | A                   |
| Trademark:                | NALHON              |

### Picture of product

