

# EU TYPE-EXAMINATION CERTIFICATE

according to Article 19 (c) of Regulation (EU) 2016/425 of the European Parliament and of the Council

**No. 1019-314/Q/2024**

Name of product: **Aluminum Rebar Carabiner, type YAC016S, YAC016D, YAC016T, YAC016S-CP, YAC016D-CP, YAC016T-CP**

PPE category: **III.**

Manufacturer: **Nal Hon Industrial Co., Ltd.  
No. 418, Hsi-Hu Road, Da-Li District  
41263 Taichung City  
Taiwan**

Applied standards and/or technical specification: **ČSN EN 362:2005 (identical to EN 362:2004)  
ČSN EN 12275:2013 (identical to EN 12275:2013)  
ČSN EN 365:2005 (identical to EN 365:2004)**

Base for issue of certificate: **Evaluation Report No. 1019-022117/2024 (integral part of this certificate)**

Conditions of validity: **Certificate shall only be used in conjunction with one of the conformity assessment procedures referred to Article 19 (c) point (i) or (ii) of Regulation (EU) 2016/425 of the European Parliament and of the Council.**

Validity of certificate till: **July 31, 2029**

VVUU, a.s. hereby certifies that the sample of the product mentioned above meets all the relevant essential health and safety requirements of Annex II of the Regulation (EU) 2016/425 of the European Parliament and of the Council.

August 1, 2024

Date of issue



  
Tomáš Dorazil

Deputy Director NB 1019

## Description of product

|                           | YAC016S                                                                           | YAC016D      | YAC016T | YAC016S-CP     | YAC016D-CP   | YAC016T-CP |
|---------------------------|-----------------------------------------------------------------------------------|--------------|---------|----------------|--------------|------------|
| Material:                 | AA 7075                                                                           |              |         |                |              |            |
| Gate Closing:             | Self-closing                                                                      |              |         |                |              |            |
| Gate Locking:             | Manual-locking                                                                    | Self-locking |         | Manual-locking | Self-locking |            |
| Min. Gate Opening:        | 22 mm                                                                             |              |         |                |              |            |
| Min. Static Strength (↔): | 25 kN                                                                             |              |         |                |              |            |
| Min. Static Strength (⊥): | 8 kN                                                                              |              |         |                |              |            |
| Min. Static Strength (↻): | 7 kN                                                                              |              |         |                |              |            |
| Class (acc. to EN 362):   | B                                                                                 |              |         |                |              |            |
| Class (acc. to EN 12275): | B                                                                                 |              |         |                |              |            |
| Trademark                 |  |              |         |                |              |            |

## Picture of product



Aluminum Rebar Carabiner, type YAC016S, YAC016D, YAC016T



Aluminum Rebar Carabiner, type YAC016S-CP, YAC016D-CP, YAC016T-CP